

# MATERIAL SAFETY DATA SHEET - 1

DATE OF PRINTING 12/04/2002

## PRODUCT IDENTIFICATION

DISTRIBUTOR: LANE CONCEPTS  
13641 JOHN GLENN RD #B  
APPLE VALLEY, CA 92308

TELEPHONE: (760) 247-0002

TRADE NAME: **SYN-PRO**

DOT PROPER SHIPPING NAME: MINERAL OIL

EMERGENCY TELEPHONE NUMBER: (800) 683-0037

## SECTION 1 - HAZARDOUS INGREDIENTS

None Regulated

## SECTION II - HEALTH EFFECT INFORMATION

EYE CONTACT: THIS PRODUCT IS MINIMALLY IRRITATING TO THE EYES UPON CONTACT BASED ON TESTING OF SIMILAR PRODUCTS AND/OR COMPONENTS.

SKIN CONTACT: THIS PRODUCT IS NOT EXPECTED TO CAUSE ANY SKIN IRRITATION UPON DIRECT SINGLE OR REPEATED AND PROLONGED CONTACT. HOWEVER SIMILAR CHEMICAL COMPOSITION PRODUCTS APPLIED TO THE SKIN OF LABORATORY ANIMALS IS MINIMAL TO SLIGHT DERMAL IRRITATION.

INHALATION: THIS PRODUCT HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN INHALATION HAZARD AT AMBIENT CONDITIONS. CAUTION SHOULD BE TAKEN TO PREVENT AEROSOLIZATION OR MISTING OF THIS PRODUCT. THE PERMISSIBLE EXPOSURE LIMIT (PEL) AND THRESHOLD LIMIT VALUE (TLV) FOR THIS PRODUCT AS OIL MIST IS MG/M3. EXPOSURES BELOW 5 MG/M3 APPEAR TO BE WITHOUT SIGNIFICANT HEALTH RISK. THE SHORT-TERM EXPOSURE LIMIT FOR THIS PRODUCT AS AN OIL MIST IS 10 MG/M3. SEE HEALTH DATA SECTION.

INGESTING: INGESTING IS RELATIVELY NONTOXIC UNLESS ASPIRATION OCCURS, ASPIRATION MAY LEAD TO CHEMICAL PNEUMONITIS WHICH IS CHARACTERIZED BY PULMONARY EDEMA HEMORRHAGE AND MAY BE FATAL. SIGNS OF LUNG INVOLVEMENT INCLUDE INCREASED RESPIRATORY RATE, INCREASED HEART RATE, AND A BLUISH DISCOLORATION OF THE SKIN. SOUGHING, CHOKING, AND GAGGING ARE OFTEN NOTED AT THE TIME OF ASPIRATION. GASTROINTESTINAL DISCOMFORT MAY DEVELOP, FOLLOWED BY VOMITING WITH A FURTHER RISK OF ASPIRATION. THIS PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND DIARRHEA. SEE HEALTH DATA SECTION.

HEALTH DATA: EXPOSURE TO A LARGE SINGLE DOSE, OR REPEATED SMALL DOSES OF MINERAL OIL BY INHALATION, ASPIRATION, OR INGESTION LEADING TO ASPIRATION CAN LEAD TO LIPID PNEUMONIA OR LIPID GRANULOMA. THESE ARE LOW-GRADE, CHRONIC, LOCALIZED TISSUE REACTIONS WHICH ARE NOT FATAL. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS. THE INTERNAL, AGENCY FOR RESEARCH ON CANCER (IARC) HAS CONCLUDED THAT HIGHLY REFINED MINERAL OILS ARE GROUP 3 SUBSTANCES, \*NOT CLASSIFIABLE AS THE THEIR CARCINOGENICITY TO HUMANS, \*BASED ON INADEQUATE HUMAN AND ANIMAL EVIDENCE, IARC HAD ALSO CONCLUDED THAT THERE IS NO EVIDENCE FOR THE CARCINOGENICITY TO INTRAPERITONEAL INJECTION. THIS SUBSTANCE IS NOT CARCINOGENIC ACCORDING TO THE OSHA HAZARD COMMUNICATION STANDARD.

## SECTION III - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER AND CONTINUE FLUSHING UNTIL IRRITATION SUBSIDES. IF MATERIAL IS HOT, TREAT FOR THERMAL BURNS AND TAKE VICTIM TO HOSPITAL.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING IF MATERIAL IS HOT, SUBMERGE INJURED AREA IN COLD WATER. IF VICTIM IS SEVERELY BURNED, REMOVE TO HOSPITAL IMMEDIATELY.

## MATERIAL SAFETY DATA SHEET - 2

INHALATION (BREATHING): THIS PRODUCT HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN INHALATION EXPOSURE AT AMBIENT TEMPERATURE.

INGESTION (SWALLOWING): MAY ACT AS A LAXATIVE. DO NOT INDUCE VOMITING DUE TO ASPIRATION HAZARD. IF VOMITING OCCURS LOWER HEAD BELOW KNEES TO AVOID ASPIRATION. SEEK IMMEDIATE MEDICAL ATTENTION.

### SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION: IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, ADEQUATE VENTILATION IN ACCORDANCE WITH GOOD ENGINEERING PRACTICE MUST BE PROVIDED TO MAINTAIN CONCENTRATIONS BELOW THE SPECIFIED EXPOSURE OR FLAMMABILITY LIMITS.

RESPIRATORY PROTECTION: RESPIRATORY PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE, IF VAPOR OR MISTS IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, USE AN ORGANIC VAPOR RESPIRATOR WITH A DUST AND MIST FILTER. ALL RESPIRATORS MUST BE NIOSH CERTIFIED. DO NOT USE COMPRESSED OXYGEN IN HYDROCARBON ATMOSPHERES.

SKIN PROTECTION: NO SKIN PROTECTION IS REQUIRED FOR SINGLE, SHORT DURATION EXPOSURES, FOR PROLONGED OR REPEATED EXPOSURES, USE CLOTHING (BOOTS), GLOVES, APRONS, ETC.) OVER PARTS OF THE BODY SUBJECT TO EXPOSURE. IF HANDLING HOT MATERIAL, USE INSULATED PROTECTIVE CLOTHING (BOOTS, GLOVES, APRONS, ETC.)

EYE PROTECTION: EYE PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE, IF MATERIAL IS HANDLED SUCH THAT IT COULD BE SPLASHED INTO EYES, WEAR PLASTIC FACE SHIELD OR SPLASH-PROOF SAFETY GOGGLES.

OTHER: CONSUMPTION OF FOOD AND BEVERAGE SHOULD BE AVOIDED IN WORK AREAS WHERE HYDROCARBONS

### SECTION V - REACTIVE DATA

REACTIVITY: STABLE

CONDITIONS AFFECTING REACTIVITY: NONE

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

INCOMPATIBILITY MATERIALS TO AVOID: MAY REACT WITH STRONG OXIDIZING AGENTS

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID: NONE

### SECTION VI - SPILL OR LEAK PROCEDURE

PRECAUTIONS IN CASE OF RELEASE OR SPILL: DO NOT ALLOW TO ENTER SEWERS OR WATERCOURSES. REMOVE ALL SOURCES OF IGNITION. ABSORB WITH APPROPRIATE INERT MATERIAL SUCH AS CLAY, SAND, ETC. LARGE SPILLS MAY BE PICKED UP USING VACUUM PUMPS, SHOVELS, BUCKETS, OR OTHER MEANS AND PLACED IN DRUMS OR OTHER SUITABLE CONTAINERS.

WASTE DISPOSAL METHOD - DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

### SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS: DO NOT TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAMES, OR OXIDIZING MATERIALS. THIS PRODUCT IS NOT CLASSIFIED AS HAZARDOUS UNDER DOT REGULATIONS. FIRE EXTINGUISHERS SHOULD BE KEPT READILY AVAILABLE. SEE NFPA 30 AND OSHA 1910.106--FLAMMABLE AND COMBUSTIBLE LIQUIDS.

# MATERIAL SAFETY DATA SHEET - 3

## SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

NFPA HAZARD CLASS -

HEALTH HAZARD:	1	HAZARD RANKING
FLAMMABILITY:	1	0 - LEAST
REACTIVITY:	0	1 - SLIGHT
OTHER:	0	2 - MODERATE
		3 - HIGH
		4 - EXTREME

EXTINGUISHING MEDIA: USE DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.

FIRE AND EXPLOSION HAZARDS: DENSE SMOKE MAY BE GENERATED WHILE BURNING. CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER OXIDES MAY BE GENERATED AS PRODUCTS OR COMBUSTION.

SPECIAL FIRE FIGHTING PROCEDURES: WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING WATER OR FOAM AS FROTHING MAY OCCUR, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

## SECTION IX - PHYSICAL DATA

BOILING RANGE: 580F - 600F

VAPOR PRESSURE: N/A

SOLUBILITY: SOLUBLE IN HYDROCARBONS

SPECIFIC GRAVITY (60F/60F): 0.84

APPEARANCE: CLEAR LIQUID

ODOR: MILD ODOR

EVAPORATION RATE (n - BuOAc = 1): 0.1

% VOLATILE: NIL @ AMBIENT TEMPERATURE

VAPOR DENSITY: N/A

BULK DENSITY (LB/GAL): VARIES

FLASH POINT: 204°

TEST METHOD: 1010 PENSKEY CLOSED CUP

## SECTION X - PRECAUTIONARY WARNING

THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PRACTICAL PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THE PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THE INFORMATION AND PRODUCT ARE FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE HIS OWN DETERMINATIONS AS TO THE SUITABILITY OF THE PRODUCT FOR HIS PARTICULAR PURPOSE AND ON THE CONDITION THAT HE ASSUME THE RISK OF HIS USE THEREOF.