

MATERIAL SAFETY DATA SHEET

N/T = Not Tested

N/A = Not Applicable

(Prepared According to 29 CFR 1910.1200)

Effective Date: 10-05-03

SECTION 1 - PRODUCT IDENTIFICATION

Product Name:	6-HOUR HARDENER	Chemical Family:	Polyetherdiamines	NPCA Hazardous Materials	
Generic Name:		Formula:	Proprietary	Identification System	
Suppliers Name:	Pro's Choice	Phone Number:		Health	0
Suppliers Address:	13641 John Glenn Rd #B	Emergency During Transport Only:	800-683-0037	Flammability	1
	Apple Valley, CA 92308	At All Other Times - Plant Phone:	760-247-0002	Reactivity	0
Proper Shipping Name:	Pro's Choice Ball Plug			Max Personal Protection	C

SECTION 2 - INGREDIENTS

CHEMICAL NAME	CAS NO.	WT.%	PEL	TLV
Nonylphenol	84852153	<60	N/A	N/A
Poloxypropylenediamine	9046-10-0	<20	N/A	N/A
Proprietary Ingredients	Trade Secret	>40	N/A	N/A

The product contains the following toxic chemicals subject to the reporting requirements if section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

CAS#	Chemical Name	Percent by Weight
	N/A	

SECTION 3 - PHYSICAL DATA

Boiling Range (F): N.D.A.
Vapor Pressure: N/A
% Volatile: Slight
Specific Gravity: 0.98
Physical Description: Clear Liquid

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): >400°
Upper Explosive Limit: N/A Lower Explosive Limit: N/A
Extinguishing Media: Regular Foam or dry chemical or carbon dioxide.
Special Fire Fighting Procedures: Stay upwind. Wear at least full bunker gear and SCBA.
Unusual Fire and Explosive Hazards: NONE

SECTION 5 - REACTIVITY DATA

Stability: Stable
Hazardous Polymerization: Will Not Occur
Conditions to Avoid: Exposures of 600° and above. Strong oxidizing materials or epoxy resins under uncontrolled conditions.
Hazardous Decomposition Product: Carbon Monoxide, aldehydes and acids may be formed during combustion. Reaction with resin agents may produce considerable heat.

SECTION 6 - STORAGE AND HANDLING INFORMATION

Precautions to be Taken in Handling and Storage: Store in a cool, dry place.
Provide adequate ventilation that will keep airborne concentration at a minimum.

SECTION 7 - HEALTH HAZARDS AND FIRST AID

Primary Source of Entry:

First Aid Procedure:

Skin: Can cause irritation. Significant, prolonged or repeated exposure can cause severe irritation.
Eyes: Will cause eye irritation and burning sensation. Repeated contact can cause cornea damage.
Inhalation: Can enflame the G.I. tract.
Ingestion: May cause nausea, vomiting, and abdominal pain, and may be harmful.

Skin: Flush well with soap and water. If, symptoms persist, consult a physician.
Eyes: Immediately flush with water for 15 minutes. Get medical attention promptly.
Inhalation: Move to fresh air. Give oxygen if breathing is difficult. Call a physician.
Ingestion: Give large quantities of water to dilute material. Do not induce vomiting. Call a physician.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection: None required, but use SCBA in areas with high vapor concentrations.
Protective Gloves: Butyl or Rubberized for prolonged use.
Other protective equipment: Rubberized gloves, rubberized apron.

Ventilation: Use with adequate ventilation.
Eye Protection: Safety goggles or glasses.

SECTION 9 - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:

Waste Disposal Method:

Spills: Small spills can be flushed with large amounts of water.
Large spills should be collected for disposal.

Follow federal, state, and local regulations governing the disposal of waste materials.